## SILVENT



## PNEUMATIC MUFFLER SILVENT SIS-20

Item number: 70200169111, 70200269111

SILVENT SIS-20: Silvent's pneumatic mufflers are designed to handle sensitive systems with large flows that require minimal flow restriction. The mufflers are compact in size, provide extremely effective noise suppression and feature a built-in warning indicator that immediately shows any increase of backpressure in the system. The unique filter material is divided into numerous "noise traps" or cells and gives extremely good muffling with minimal flow restriction. These pneumatic mufflers are also suitable for continuous flow applications and can be used as a central muffler for several pneumatic valves. A built-in oil trap collects airline oil for draining and prevents oil mist exhaust. The mufflers are available in two sizes, 1 inch and 2 inch, and reduce noise levels 40-45 dB(A). They are supplied with a mounting bracket.

## **Technical data**

i centinear aaca			
Flow capacity (Nm³/h)	2480	133mm	2/3mm
Air flow (Nm³/h)	1210		
Sound level (dB(A))	94.3		
Connection	G 2"		
Connection type	Female		
Weight (kg)	2.7000		
Max temp (°C)	70		
Max op. pressure (MPa)	1.0		
Noise reduction [dB(A)]	41		

Material specification: EN 10130 DC04 DC01, EN 1.4301, HDPP, NBR, EN 1.4305, CW617N, Zn

*The value of the flow applies with continuous operation over a valve. The value of the noise reduction applies with operations over a valve.*